

SupTech TRAFFIC FILM PRE-WASH HIGH FOAM



(ES)

Champú prelavado altamente concentrado y con acción espumante. Elimina la suciedad más incrustada sobre la carrocería y vehículos industriales.

Producto especialmente formulado para la eliminación efectiva del traffic film que se deposita sobre la carrocería industrial aportando un efecto de espuma que se adhiere sobre la superficie. Su alto contenido en tensioactivos le confiere un gran poder humectante y desengrasante que disuelve y elimina todo tipo de restos grasos y suciedades difíciles.

Es importante no dejar secar nunca el producto químico sobre la carrocería, ni rociarlo sobre superficies muy calientes o mates sin antes humedecerlas y que no se exponga el vehículo al sol durante su aplicación. Tras la aplicación del producto, aclarar con agua a alta presión.

MODO DE EMPLEO

Para dosificación manual o automática se recomienda trabajar en diluciones de producto entre un 2 - 20%, en función de la suciedad a eliminar. Rociar el vehículo con el producto diluido, dejar actuar durante 1 a 3 minutos y aclarar con agua a presión. Es importante no dejar secar nunca el producto químico sobre la carrocería, ni rociarlo sobre superficies muy calientes o mates sin antes humedecerlas y que no se exponga el vehículo al sol durante su aplicación.

NORMA DE ALMACENAJE

No guardar en lugares sometido a temperaturas extremas y evitar la acción directa del sol. Conservar únicamente en el recipiente de origen. La información sobre manipulación y eliminación del producto está disponible en la Ficha de Datos de Seguridad.

PRODUCTO INDUSTRIAL. USO PROFESIONAL.

EN CASO DE ACCIDENTE CONSULTAR AL SERVICIO MÉDICO DE INFORMACIÓN TOXICOLÓGICA. TEL. [+34] 915 620 420.

INFORMACIÓN ADICIONAL DE PRODUCTO

PRESENTACIÓN FÍSICA	Líquido
COLOR	Beige
PESO ESPECÍFICO	1120 - 1140 kg/m ³
pH.....	13 - 14 (100 %)

La información contenida en la ficha ha sido elaborada a partir de nuestros conocimientos técnicos sobre el producto a la fecha de la puesta al día y se dan de buena fe al usuario. El uso de dicha información y las condiciones de utilización del producto quedan bajo la responsabilidad exclusiva del usuario, si se destinan para otro fin que no es el adecuado.

(GB)

Highly concentrated pre-wash shampoo with foaming action. Removes the most stubborn dirt from bodywork and commercial vehicles.

Product specially formulated for the effective removal of traffic film deposited on industrial bodywork, providing a foaming effect that adheres to the surface. Its high surfactant content gives it great wetting and degreasing power that dissolves and removes all types of greasy residue and stubborn dirt.

It is important to never allow the chemical product to dry on the bodywork, or spray it on very hot or matte surfaces without first moistening them, and to avoid exposing the vehicle to sunlight during application. After applying the product, rinse with high-pressure water.

DIRECTIONS FOR USE

For manual or automatic dosing, it is recommended to work with product dilutions between 2 - 20%, depending on the dirt to be removed. Spray the vehicle with the diluted product, leave it to act for 1 to 3 minutes and rinse with pressurized water. It is important never to let the chemical product dry on the bodywork, nor to spray it on very hot or matte surfaces without first moistening them and to not expose the vehicle to the sun during its application.

STORAGE INDICATIONS

Do not keep in places exposed to extreme temperatures and avoid direct contact with sunlight.

INDUSTRIAL PRODUCT. FOR PROFESSIONAL USE.

IN CASE OF ACCIDENT, CONTACT THE POISONS INFORMATION SERVICE.

ADDITIONAL PRODUCT INFORMATION

PHYSICAL APPEARANCE.....	Liquid
COLOUR	Beige
SPECIFIC WEIGHT	1120 - 1140 kg/m ³
pH.....	13 - 14 (100 %)

The information contained in this file represents the extent of our technical knowledge about the product on the day it was updated and is given to the user in good faith. Use of this information and the conditions under which the product is used are the exclusive responsibility of the user if used for purposes for which it is not suited.